

IP CRM-V DAK MODULE



when communication is **critical**

FEATURES

- 48 DAK keys provide single-touch access to stations, group calls, audio monitoring, public address zones, radio channels and telephone lines
- Each DAK is equipped with two programmable LED indicators, one red and one green. The LEDs can be used to show alarms, notifications, call requests, or any other indication required from the system
- Adjustable backlight
- Each key can be individually labeled, giving the easiest possible user interface
- Designed in line with the CRM-V

DESCRIPTION

The DAK module for CRM-V is an expansion of the CRM-V for applications where quick access to different functions is required.

The connection between the CRM-V and DAK module is completely transparent for the user. When connected, the DAK module acts as an integral part of the CRM-V station, giving access to a large number of direct access keys with related LED indicators.

One or two DAK modules can easily be connected to one CRM-V, giving a total of 52/100 DAK keys. The module is powered entirely from the CRM-V host, and requires no other connections. The CRM-V can power up to 2 DAK modules regardless of its own power source (PoE or separate 24 Vdc supply).

The STENTOFON DAK module is designed for control rooms in prisons and buildings, but it can also be used for other applications.



SPECIFICATIONS

Dimension (WxHxD):	125 x 280 x 30 mm
Weight	650 g
Temperature range	0°C - 55°C
Power	Powered over connection cable from CRM-V
Connectors	RJ45, one in and one out
Backlight	White backlight, following the luminosity of the host CRM-V
Installation	RJ45 terminated cable between CRM-V and DAK module. 2 modules can be daisy chained
Software	All software for the DAK module is located in the CRM-V

sales@ringuk.com

01353 865668

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
1008010100	IP CRM-V DAK Module	
1008098700	Flush Mount Back Box	0.5 kg

IP CRM-V DAK MDULE

ORDER NUMBER

1008010100

DOC NO

A100K10660

sales@ringuk.com

